



SC-25 Accent Powder

Description

SC-25 Accent Powder is a polymere infused powder coloring system. That provides a natural coloring effect over most concrete overlays and over stamped concrete.

- Fade Resistant
- Colors Can Be Blended

Uses

SC-25 is designed to be used as a color additive for the Texture-Crete, ALX, and MACoat Custom Finish systems.

Packaging
2 gallon pails

Color	
Slate Green	Spanish Brown
Pewter Gray	Black
Slate Blue	Terracotta
Tile Red	Mission Red
Travatan	Oxford
Rust	Sand

Advantages

- Water-Based No Odor
- User Friendly
- Many Color Variations Available

INSPECTION / PREPARATION

Inspection

Surfaces must be clean, dry and free of oil grease, curing agents, dirt, dust, or other foreign material that may prevent proper adhesion.

Preparation

When applying over Westcoat systems no preparation is necessary, apply directly to the textured surfaces. When applying over concrete the surface must be porous or rough enough to allow the product to soak in.

APPLICATION

Coverage

Coverage will vary depending on ratios used. On the average between 800 to 2000 square feet per 2 gallon bucket of SC-25.

avoid settling. The darkening or accenting can also be achieved by dry rubbing the SC-25 on to the surface with a dry sponge.

Applying Product

Depending on the desired color mix 4 to 10 parts of water and roll on to the texture with a ¾ inch nap roller and work color into the surface using a stiff brush or broom. Continue to broom the SC-25 until most of the water has evaporated or until all broom marks have dissipated. Reapply to darken or accent individual stones or tiles. Mixed SC-25 must be continuously stirred to

Dry Time

SC-25 will dry in 1 to 2 hours at 70 degrees and 50% humidity.

Clean Up

Uncured material can be removed with soap and warm water. Cured material can be removed mechanically.

LIMITATIONS

- Do not apply in temperatures below 55°F or above 95°F.
- Rain will wash away uncured acrylic products. If inclement weather threatens, cover deck to protect new application.

- Apply only over bare, pours surfaces, or Westcoat systems.
- Do a test area before you begin.
- Do not allow any Westcoat products to FREEZE.

HEALTH PRECAUTIONS

Inhalation of vapor or mist can cause headache, nausea, irritation of nose, throat, and lungs. Prolonged or repeated skin contact can cause slight skin irritation.

DISCLAIMER

PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER OF WESTCOAT, SHALL BE LIMITED SOLELY TO THE REPLACEMENT OF ANY DEFECTIVE MATERIAL OR A PAYMENT BY THE MANUFACTURER IN AN AMOUNT EQUAL TO THE COST OF THE ORIGINAL MATERIAL.



770 Gateway Center Drive San Diego, CA 92102
800 • 250 • 4519 • Fax 619 • 262 • 8606 • westcoat.com